

SPECIFICATIONS LM-VX2039-SA-TH2

LCD PANEL

Type : 19.5" IPS LCD
Display Area : 418.608(H) X 262.35 (V)mm (19.5" wide)
Resolution : WXGA+ 1440 x 900
Brightness : 250 cd/m2 (typ)
Dynamic Contrast Ratio : 80M:1
Viewing Angles : 178°/178° (typ)
Response Time : 5ms (GTG)
Backlight : 1 WLED light bar
Backlight Life : 30,000 Hrs (Min)
Colours : 16.7M (6 bit with A-FRC)
Panel Surface : Anti-Glare type, Hard-coating (3H)

INPUT SIGNAL

Frequency : Fh = 24 ~82 kHz ; Fv = 50 ~75 Hz
Sync : Separate Sync / Composite Sync / Sync on Green

COMPATIBILITY

PC : PC Compatibles (VGA up to 1440x900 Non Interlaced)
Mac : Power Mac (up to 1440x900)

CONNECTOR

Analog : DB-15 x1

POWER

Power : External Adaptor , 5.5 x 1.7 x 11 DC connector
Voltage : AC 100-240V (Universal); 50/60Hz
Consumption : 16 W
Optimize : 13 W
Conserve : 11 W

ERGONOMICS

Tilt : -5±2, 15±2 degrees

WALL MOUNT

VESA : 100mm x 100mm

OPERATING CONDITIONS

Temperature (° F / ° C) : 32°F to 104°F (0°C to 40°C)
Humidity : 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical With Stand (mm) : 453.6 mm (W) x390.4 mm (H) x 164 mm (D)
17.9" (W) x 15.4" (H) x6.5" (D)

WEIGHT

Net With Stand (kg) : 2.2 Kg (4.9 lbs)

REGULATIONS

RoHS, REACH, WEEE, CCC, CEL

PACKAGE CONTENTS

LCD Display / Adapter / Power Cable / D-Sub Video Cable / Quick Start Guide
*Actual content may differ from market to market

Lemel

